



TECHNICAL DATA SHEET PEDESTAL EH


SUPERIOR QUALITY FOR BUILDING







EH 15





TECHNICAL SPECIFICATION

Supply and installation of supports for raised flooring type "EH". The supports consist of a single polypropylene element available in three versions EH12 (diameter 150mm) EH15 (diameter 140mm) EH 20 (diameter 150mm), in the upper part there are N°4 spacer tabs having heights of 11mm respectively (EH12), 12mm (EH15) and 18mm (EH20). There is also the possibility of coupling to the bases 4 exclusive tilting balancers to compensate for any slopes of the laying area.

CHARACTERISTICS:

Heights 12mm 15mm 20mm not adjustable. Prepared for the insertion of one or more tilting balancers with a height of 5mm. Sectionable support in 2 or 4 parts in case of need on the wall or in the corners.

RAW MATERIAL:

Polypropylene

ENVIRONMENTAL IMPACT:

recyclable material - not dangerous

APPLICATIONS SURFACES:

On any waterproofing membrane On any insulating hard panel On any compact and solid surface

APPLICATIONS AREA:

Can be used with any prefabricated self supporting element for outdoor flooring

GENERAL CHARACTERISTICS & PROPERTIES

	UNIT	VALUE	TOLERANCE +/-
BASE DIAMETER	mm	150	+/- 1.0
BASE THICKNESS	mm	1.5	+/- 0.2
SURFACE OF THE BASE	cmq	177	+/- 5
TABS THICKNESS	mm	4	+/- 0.2
TABS HEIGHT	mm	11 - 12 - 18	+/- 0.2
SHORE	Shore d	70	+/- 3
FIRE REACTION*	UNI-EN 13501-1:2009	CLASSE "E"	
LOW T(°C) REACTION	°C	-40	

^{*}Tests made by Giordano S.p.A. Institute of Bellaria-Igea Marina (RN)-Italy



TECHNICAL DATA SHEET PEDESTAL *EH*

ITEMS CHARACTERISTICS & PROPERTIES

EH12_E000012004	UNIT	VALUE	+/- N°	PACK/STORAGE	
HEIGHT	mm	12	+/- 1,0	PIECES PER BOX	250
WEIGHT	kg	0.046	+/- 5 %	BOXES PER PALLET	20
MAX CENTRAL COMPRESSION RESISTANCE*	kN	61.26	/	BOX DIMENSION	40x62x40cm
The code refers to the model with 4 mm thick fins, 2 and 3 mm fins available on request				BOX WEIGHT	12.5kg
				PALLET	80x120cm
				PCS PER PALLET	5000

EH15_E000015000	UNIT	VALUE	+/- N°	PACK/STORAGE	
HEIGHT	mm	15	+/- 1,0	PIECES PER BOX	200
WEIGHT	kg	0.046	+/- 5 %	BOXES PER PALLET	20
MAX CENTRAL COMPRESSION RESISTANCE*	kN	55.13	/	BOX DIMENSION	40x62x40cm
				BOX WEIGHT	10.20kg
The code refers to the model with 4 mm thick fins, 2 and 3 mm fins available on request			PALLET	80x120cm	
				PCS PER PALLET	4000

EH20_E002020000	UNIT	VALUE	+/- N°	PACK/STORAGE	
HEIGHT	mm	20	+/- 1,0	PIECES PER BOX	150
WEIGHT	kg	0.073	+/- 5 %	BOXES PER PALLET	20
MAX CENTRAL COMPRESSION RESISTANCE*	kN 7	75.90	/	BOX DIMENSION	40x62x40cm
				BOX WEIGHT	11.95kg
The code refers to the model with 4 mm thick fins, 2 and 3 mm fins available on request			PALLET	80x120cm	
				PCS PER PALLET	3000

^{*}Tests made by Civil and Environmental Department of University of Padova. 1 kN = 102 kg

The packaging of the supports consists of cardboard boxes. The final packaging of the pallets is made with the wrapping of a polyethylene film. Indoor storage, protected from precipitation, is recommended.

INSTALLATION METHOD

The product is laid dry, without the need for adhesives or other types of fixings.

Eterno Ivica. All rights reserved.

CTC TO IVICA

CTC TO I