
























| | STANDARD | RESULT |
|--|--|--|
| Dimensions and basic data | | |
|  SIZE | EN ISO 24342 | Plank: 120 x 600 mm |
|  THICKNESS | EN ISO 24346 | 6.5 mm (5.5 mm spc + 1 mm integrated backing) |
|  WEAR LAYER | EN ISO 24340 | 0.70 mm |
| LOCKING METHOD | | Click-system |
| SURFACE TREATMENT | | PU coating + protected with aluminium oxide (anti-scratch) and stain resistant technology. |
| CORE | | Sound reducing water resistant rigid core, SPC |
| Technical data - CE EN 14041 | | |
|  BEVELLED EDGE | MICRO | 4 Sides |
|  MASS | | 10.80 kg/m ² |
|  STANDARDS | EN 16511 | |
|  CLASSIFICATION | EN 685 / EN ISO 10874 - Light industrial | 42: Light industrial general |
| | EN 685 / EN ISO 10874 - Commercial | 33: Commercial heavy |
| | EN 685 / EN ISO 10874 - Domestic | 23: Domestic heavy |
|  REACTION TO FIRE | EN 13501-1 | Bfl-S1 |
|  STAINING RESISTANCE | EN 438-2 | Group 1/2/3: Degree 5 |
|  LIGHT FASTNESS | EN ISO 105-B02 | > 6 |
|  DIMENSIONAL STABILITY | EN 434 / EN ISO 23999 | ≤ 0.10 % |
|  ACOUSTIC IMPACT - NOISE REDUCTION | EN ISO 717-2 / EN ISO 140-8 | ΔL _w = 19 DB |
|  ELECTRICAL BEHAVIOR - BODY VOLTAGE | EN 1815 | Pass |
|  INDENTATION - RESIDUAL | EN ISO 24343-1 | ≤ 0.10 mm |
|  CASTOR CHAIR | ISO 4918 | Pass |
|  THERMAL RESISTANCE | EN 12667 | < 0.122 (m ² K/W) |
|  SLIP RESISTANCE* | EN 13893 / DIN 51130 | DS R9 |
| WEAR RESISTANCE | EN 660-2 / EN 649 | Class T |
|  IMPACT RESISTANCE | EN 13329 | Pass |
| CLICK TENSION | ISO 24334 | Short side: 14.7 kn/m - Long side: 3.7 kn/m |
|  SWELLING | ISO 24336 | Pass |
|  FLOOR HEATING | Appropriate for standard heating systems in cement flooring. | Not appropriate for heating electric films. |
| Dangerous substances | | |
|  VOC EMISSION | French/Belgian/German Regulations | Pass |
|  FORMALDEHYDE EMISSION | EN 717-1 | E1 |
| REACH | | Friendly reach compliant |
|  PCP | EN 12673 | Pass |